

Application No. 09/061,441
Response dated December 15, 2003
to Office Action of 08/13/2003

In the Claims

Please cancel claims 33 through 45, without prejudice or disclaimer, to place the application in condition for formal allowance with allowed claims 18-24, 31 and 32.

This listing of claims will replace all prior versions of the claims of this application:

Listing of Claims

Claims 1 – 17 (cancelled)

Claim 18 (previously presented): In a communications system,

... a first antenna, and a first input amplifier for amplifying signals received by said first antenna;

... a second antenna, and a second input amplifier for amplifying signals received by said second antenna;

... an intermediate frequency stage connected to said second input amplifier; and

... a selector disposed between said first input amplifier and said intermediate frequency stage and between said second antenna and said second input amplifier for selecting operation of the communications system between said first and second antennas,

wherein said first input amplifier includes a feedback loop for altering the operational characteristics of said first input amplifier in receiving mode.

Claim 19 (previously presented): In a communications system as claimed in claim 18, wherein said feedback loop includes a switch for selectively activating said feedback loop.

Application No. 09/061,441
Response dated December 15, 2003
to Office Action of 08/13/2003

Claim 20 (previously presented): In a communications system as claimed in claim 18, wherein said feedback loop is a closed loop.

Claim 21 (previously presented): In a communications system,

a first antenna, and a first receiving amplifier for amplifying signals received by said first antenna;

a second antenna, and a second receiving amplifier for amplifying signals received by said second antenna;

an intermediate frequency stage connected to said second receiving amplifier; and

a selector disposed between said first receiving amplifier and said intermediate frequency stage and between said second antenna and said second receiving amplifier for selecting operation of the communications system between said first and second antennas;

said first and second receiving amplifiers providing plural signal receiving paths of different signal processing characteristics in a receiver diversity architecture wherein for a given incoming radio signal, either of the respective signal receiving paths are respectively selectably operable.

Claim 22 (previously presented): In a communications system as claimed in claim 21, said first receiving amplifier includes a feedback loop for altering the operational characteristics of said first receiving amplifier.

Claim 23 (previously presented): In a communications system as claimed in claim 22, said feedback loop includes a switch for selectively activating said feedback loop, to selectively change the signal processing characteristics for the incoming radio signal.

Claim 24 (previously presented): In a communications system as claimed in claim 22, said feedback loop is a closed loop.

Application No. 09/061,441
Response dated December 15, 2003
to Office Action of 08/13/2003

Claims 25 – 30 (cancelled).

Claim 31 (previously presented): In a communications system,
a first antenna and a second antenna
for selective operation in
receiving mode;
an input amplifier having two respective active operating conditions for amplifying
signals received by said first
antenna when selected for
operation in respective first active receiving modes;
an intermediate frequency stage
for selective connection with the
first antenna and the input amplifier in the first active
receiving modes, and for
selective connection to the
second antenna in a second active
receiving mode;
a selector system for selecting
between the first active receiving
modes and the second active
receiving mode;
wherein said input amplifier includes a feedback loop which is selectively closed in one
of the first active receiving modes, and is selectively open in another of the first active
receiving modes, such that the receiving path from the first antenna to the intermediate
frequency stage in the respective first active receiving modes selectively has two
respective different signal processing characteristics for a given incoming radio signal at
the first antenna, the input amplifier in addition to having two active operating conditions

Application No. 09/061,441
Response dated December 15, 2003
to Office Action of 08/13/2003

providing two different signal processing characteristics of said receiving path from the first antenna to the intermediate frequency stage, having a deactivated condition when said selector system selects the second active receiving mode.

Claim 32 (previously presented): In a communications system as claimed in claim 31, the signal receiving path from the first antenna to the intermediate frequency stage in the first receiving mode has a different signal processing characteristic than the signal receiving path from the second antenna to the intermediate frequency stage in the second receiving mode, for the case where the feedback loop is selectively closed, and for the case where the feedback loop is selectively open.

Claims 33-45 (canceled)